

TT-300



TT-300
Ultrasonic wall thickness gauge



Features

- Easy to operate ultrasonic wall thickness gauge for metals, glass, plastics
- Display resolution menu selectable
- Automatic zero setting
- Two-point calibration possible
- LCD display with backlight
- Min. mode for minimum thickness measurement
- Mm/inch selectable
- Data output RS-232
- Large internal memory for 500 readings
- Including protection case, couplant and carrying case

Technical specifications

Measuring range (steel)	5.0mm - 300.0mm with 2 MHz transducer 1.2mm - 225.0mm with 5 MHz transducer
Tolerance	$\pm 1\%H + 0.1\text{ mm}$ (H means the thickness of tested piece)
Transducer frequency	Standard 5 MHz, diameter probe 10mm
Display resolution	Menu selectable, low 0.1mm, high 0.01mm
Measuring units	mm/inch selectable
Sound velocity range	1000 - 9999m/s
Display	LCD with backlight
Display Min. mode	Display current thickness or minimum thickness (menu selectable)
Alarm function	Minimum / Maximum limits exceeding alarm
Calibration setting	Automatic zero setting, two-point calibration possible
Data output	RS-232 serial port, Baud rate selectable to printer or pc
Memory	Storage of 500 thickness readings
Surface temperature	Standard -10°C to +60°C, (high temperature see TT-320)
Battery indicator	Low battery indicator
Power supply	2 pcs AA batteries 1.5V
Operation time	With backlight 60 hours continuously, Without backlight 100 hours continuously
Dimensions	152mm x 74mm x 35mm
Weight	370gr

Standard delivery

- Instrument
- Integrated steel calibration plate
- Transducer 5 MHz
- Batteries AA 1.5V (2 pcs)
- Ultrasonic couplant
- Manual
- INNOVATEST® certificate
- Carrying case

Optional accessories

- Transducers for special applications
- TA-230 printer with cable
- Software Dataview TT-300

TA-230 MICRO PRINTER



Order details

TT-300 Ultrasonic wall thickness gauge

Kapcsolat, bővebb információ:



Sidex Trade Kft.

1224 Budapest, Dózsa György út 105.
TT Ipartelep (volt Mechanikai Művek)
Tel : (+36-1) 424-1705, Mobil: (+36-30) 9349-611
Fax :(+36-1) 424-1704
Web: <http://www.sidex.hu> – E-mail: info@sidex.hu

CORPORATE HEAD OFFICE

INNOVATEST Europe BV
mANuFACTuRING, DISTRIBuTION & SERVICE
Borgharenweg 140
6222 AA Maastricht (The Netherlands)
Phone: +31 43 3520060
Fax: +31 43 3631168
E-mail: info@innovatest-europe.com
Website: www.innovatest-europe.com

BRANCHE OFFICES

INNOVATEST Benelux BVBA
SAIES & SERVICE
Phone: +32 12 779002
Fax: +32 12 779003
E-mail: info@innovatest-benelux.com
Website: www.innovatest-europe.com

INNOVATEST Shanghai Co., Ltd.
ASIA & CHINA SAIES & SERVICE
Building 2, No.123, 1165 Nong Jindu Road,
South Metropolis Industrial Park
Minhang District, Shanghai, P.R. China
Zip code: 201108
E-mail: info@innovatest-shanghai.com
Website: www.innovatest-shanghai.com

Changes in products and/or product specifications can emerge due to new technologies and continuous development.

We reserve the right to change or modify specifications of products without prior notice.

We recommend you to contact our sales office for up-to-date information.

© All rights reserved