

IMPACT TH-170 Series



IMPACT TH-170 Series Portable Dynamic hardness testers



Features

The world famous IMPACT™ series, part of the unbeatable series of TIME dynamic Leeb hardness testers offer very affordable, but accurate hardness testing solution for on-site testing in workshops and in field operation. The units assure accurate and reliable measurement. USB to computer. Any metallic products with a minimum solid mass starting from 0.5kg can be tested according to the Leeb principle. The display shows hardness values in all common scales, such as HRC, HRB, HRA, HV, HB, HS, and HLD.

The instrument is equipped with replaceable batteries providing 16 hours continuous operation.

- Dynamic rapid hardness test procedure
- TH-170 Impact device D integrated
- TH-172 Impact device C applying low impact energy for surface hardened components and thin walled components
- TH-174 Impact device DL for testing in confined spaces
- Wide measuring range
- Direct display of hardness Rockwell HRB, HRC, HRA, Vickers HV, Brinell HB, Shore HS, Leeb HL
- For most metallic materials
- Automatic gravity compensation for testing at any angle
- Simple handling and low test expenditure
- High accuracy $\pm 0.5\%$
- Clear LCD display showing all functions and parameters
- Conforms to ASTM A 956 and DIN 50156
- USB connection to PC

Technical specifications

Hardness parameter	HRC, HRA, HRB, HV, HB, HS, HL
Accuracy	Within ± 6 HLD (TH-170), Within ± 12 HLC (TH-172), Within ± 12 HLDL (TH-174)
Statistics	Average (max. 270 in 9 groups)
Output	USB
Max. Surface roughness of workpiece	1.6 μ m (Ra) (TH-170/174), 0.4 μ m (Ra) (TH-172)
Impact device integrated	D (TH-170), C (TH-172), DL (TH-174)
Needle front section of DL-device (TH-174)	Diameter = 4.2mm, Length = 50mm
Max. hardness value	940HV (TH-170), 1000HV (TH-172), 950HV (TH-174)
Workpiece radius (convex/concave)	Rmin = 50mm, (with support ring Rmin= 10mm)
Workpiece minimum weight	2kg - 5kg on solid support (TH-170/174), 0.05kg - 2kg with coupling paste 0.5 - 1.5kg on solid support (TH-172), 0.02 - 0.5kg with coupling paste
Workpiece min. thickness coupled	5mm (TH-170/174); 1mm (TH-172)
Workpiece min. case hardened depth	0.8mm (TH-170/174), 0.2mm (TH-172)
Indentation depth	See page: Impact devices data
Continuous working time	150 h (without backlight)
Power	Batteries AAA (2 pcs)
Operating temperature	0°C to 40°C
Overall dimensions	155mm x 24mm x 55mm (TH-170/172), 210mm x 24mm x 55mm (TH-174)
Weight	180gr (TH-170/172) or 200gr (TH-174)

Standard delivery

- Instrument with integrated impact device type D, C or DL
- Hardness test block with Leeb value and HRC value
- AAA Batteries (2pcs)
- Cleaning brush
- Coupling paste
- Support ring small
- USB communication cable
- USB driver cd
- INNOVATEST® certificate
- Manual
- Carrying case

Optional accessories

- DKD Reference hardness blocks
- Support rings for convex, concave and spherical surfaces (only TH-170/172)

Order details

- TH-170** Dynamic hardness tester with integrated impact device D
- TH-172** Dynamic hardness tester with integrated impact device C
- TH-174** Dynamic hardness tester with integrated impact device DL

Kapcsolat, bővebb információ:



Sidex Trade Kft.

1224 Budapest, Dózsa György út 105.
TT Ipartelep (volt Mechanikai Művek)
Tel : (+36-1) 424-1705, Mobil: (+36-30) 9349-611
Fax :(+36-1) 424-1704
Web: <http://www.sidex.hu> – E-mail: info@sidex.hu

CORPORATE HEAD OFFICE

INNOVATEST Europe BV
mANuFACTuRING, DISTRIBuTION & SERVICE
Borgharenweg 140
6222 AA Maastricht (The Netherlands)
Phone: +31 43 3520060
Fax: +31 43 3631168
E-mail: info@innovatest-europe.com
Website: www.innovatest-europe.com

BRANCHE OFFICES

INNOVATEST Benelux BVBA
SAIES & SERVICE
Phone: +32 12 779002
Fax: +32 12 779003
E-mail: info@innovatest-benelux.com
Website: www.innovatest-europe.com

INNOVATEST Shanghai Co., Ltd.
ASIA & CHINA SAIES & SERVICE
Building 2, No.123, 1165 Nong Jindu Road,
South Metropolis Industrial Park
Minhang District, Shanghai, P.R. China
Zip code: 201108
E-mail: info@innovatest-shanghai.com
Website: www.innovatest-shanghai.com

Changes in products and/or product specifications can emerge due to new technologies and continuous development.

We reserve the right to change or modify specifications of products without prior notice.

We recommend you to contact our sales office for up-to-date information.

© All rights reserved