

TT-210



TT-210 Coating thickness gauge



Features

- Easy to use
- Automatic substrate recognition
- Automatic calculation: Mean/Max/Min/No./S.Dev
- Upper-lower limit setting and sound alarm
- Data output RS-232 to printer TA-230 or PC
- Storage function for 500 measuring results
- Measurement modes: continuous/single
- Battery operated
- Automatic selection of measuring methods
- Upper-lower limit setting and sound alarm
- 2 stop ways: Manual/automatic

Technical specifications

Operating principle	Magnetic induction, eddy current	
Measurement range	0 μ m to 1250 μ m, 0 μ m ~ 40 μ m	
Measuring system	Selectable mm/inch	
Minimum resolution	0.1 μ m (coating thickness <100 μ m)	
Measuring accuracy		
Zero-point calibration	$\pm(3\%H+1\mu\text{m})\mu\text{m}$ (F probe), $\pm(3\%H+1.5\mu\text{m})\mu\text{m}$ (N probe)	
Two-point calibration	$\pm(1\%\sim 3\%H+1\mu\text{m})\mu\text{m}$ (F probe), $\pm(1\%\sim 3\%H+1.5\mu\text{m})\mu\text{m}$ (N probe) (H= nominal value)	
Sample	Min. radius workpiece	Convexity 1.5 (F probe), convexity 3 (N probe)
	Min. measuring area	$\varnothing 7\text{mm}$ (F probe), $\varnothing 5\text{mm}$ (N probe)
	Min. sample thickness	0.5mm (F probe), 0.3mm (N probe)
Statistics TT-210	Average (MEAN), MAX., MIN., number of measurements (NO.), standard deviation (S.Dev)	
Power supply	Battery AAA 1.5V (2 pcs)	
Display	LCD with backlight	
Dimensions	110mm x 50mm x 23mm	
Weight	100gr	

Standard delivery

- Instrument
- Calibration foil set
- Substrate
- AAA 1.5V battery (2 pcs)
- Manual
- INNOVATEST® certificate
- Carrying case

Optional accessories

- Printer TA-230 with cable
- Connecting cable
- Dataview software

TA-230 MICRO PRINTER



Order details

TT-210 Coating thickness gauge with integrated F/FN probe

Kapcsolat, bővebb információ:



Sidex Trade Kft.

1224 Budapest, Dózsa György út 105.
TT Ipartelep (volt Mechanikai Művek)
Tel : (+36-1) 424-1705, Mobil: (+36-30) 9349-611
Fax :(+36-1) 424-1704
Web: <http://www.sidex.hu> – E-mail: info@sidex.hu

CORPORATE HEAD OFFICE

INNOVATEST Europe BV
mANuFACTuRING, DISTRIBuTION & SERVICE
Borgharenweg 140
6222 AA Maastricht (The Netherlands)
Phone: +31 43 3520060
Fax: +31 43 3631168
E-mail: info@innovatest-europe.com
Website: www.innovatest-europe.com

BRANCHE OFFICES

INNOVATEST Benelux BVBA
SAIES & SERVICE
Phone: +32 12 779002
Fax: +32 12 779003
E-mail: info@innovatest-benelux.com
Website: www.innovatest-europe.com

INNOVATEST Shanghai Co., Ltd.
ASIA & CHINA SAIES & SERVICE
Building 2, No.123, 1165 Nong Jindu Road,
South Metropolis Industrial Park
Minhang District, Shanghai, P.R. China
Zip code: 201108
E-mail: info@innovatest-shanghai.com
Website: www.innovatest-shanghai.com

Changes in products and/or product specifications can emerge due to new technologies and continuous development.

We reserve the right to change or modify specifications of products without prior notice.

We recommend you to contact our sales office for up-to-date information.

© All rights reserved